



# MASTER LEDspot MV

MASTER LEDspotMV 7-50W GU10 4200K 40D

Delivering a warm, halogen-like accent beam, MASTER LEDspot GU10 is ideal for spot lighting (track, corridors, lift lobbies, display cases and cabinets) in the hospitality industry. It is particularly suited to public areas such as lobbies, corridors, stairwells, where the light is on 24/7. MASTER LED spot GU10 delivers huge energy savings and minimises maintenance cost without any compromise on brightness, enabling hospitality owners to achieve a return on their investment within one year. Compatible with most existing fixtures with a GU10 holder and designed as a retrofit replacement alternative for 35 and 50 W halogen lamps.

## Product data

### • Product Data

Order code	860450 00
Full product code	872790086045000
Full product name	MASTER LEDspotMV 7-50W GU10 4200K 40D
Order product name	MASTER LEDspotMV 7-50W GU10 4200K 40D
Pieces per pack	1
Packs per outerbox	6
Bar code on pack - EAN1	8727900860450
Bar code on outerbox - EAN3	8727900860467
Logistic code(s) - 12NC	929000164301
Net weight per piece	0.116 kg

### • General Characteristics

Cap-Base	GU10
Bulb	Reflector [Reflector]
Average Lifetime	40000 hr

### • Electrical Characteristics

Wattage	7 W
---------	-----

Wattage Technical	7 W
Voltage	240 V
Line Frequency	50-60 Hz
Lamp Current mA	45 mA
Dimmable	Yes


### • Light Technical Characteristics

Colour Code	CW
Colour Designation	Cool White
Beam Angle	40 D
Beam Description	40D [Medium beam]
Correlated Color Temperature	4200 K
Luminous Flux	270 Lm
Luminous Intensity	540 cd
Colour rendering index	80
Colour Temperature	4200 K [CCT 4200K]

### • Product Dimensions

Diameter D	50.2 mm
Overall Length C	80.5 mm

## Dimensional drawing



Product	C (Norm)	D (Norm)
LED 7W 7-50W GU10 4200K 240V 40D Dimm	-	-



© 2010 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2010, April 30  
data subject to change