



Product Description:

ANOVI UNIVERSAL 6W 200mm Recessed/Surface Dimmable Colour Switchable Downlight Fixed Square Matt Black

ANOVI UNIVERSAL BOXE LED ceiling light 200mm square matt black. Mounted with LED UP UNIVERSAL SWITCH white 2700K/3000K/4000K, CRI90, 6W, 500/525/600lm (88lm/W), low luminance honeycomb 60°, 230VAC/27VDC. Lifespan: 35,000 hours. Dimmable: Yes, TRIAC dimming. Protection class II/III, IP20, 100mm wired, H05S-K. Installation/installation method: surface-mounted. Compatible insulation(s): no. Dimensions: 66x66mm. Fixing type: screws onto the support. Material: aluminum. Operating temperatures: -20°C/

| SKU Code | Wattage | Colour         | Lumens      | Lumens/Watt  | Beam Angle | Finish Colour | SKU Type |
|----------|---------|----------------|-------------|--------------|------------|---------------|----------|
| 29111016 | 6       | 2700/3000/4000 | 500/525/600 | 8.34209e+007 | 60         | Matt Black    | Dimmable |
|          |         |                |             |              |            |               |          |
|          |         |                |             |              |            |               |          |

Polar Curve

## Feature & Benefits

Line Drawing

- Colour switchable between 2700/3000/4000K
- CRI90

- 35000hr lifetime
- 5 year warranty

Colour

• SDCM5

## **Product Specs:**

| Input Voltage            | ~230V AC |
|--------------------------|----------|
| IP Rating                | IP20     |
| Width (mm)               | 66       |
| Height (mm)              | 200      |
| Operating Temp. (Min) °C | -20°C    |

| Input Frequency          | 50/60HZ    |  |  |
|--------------------------|------------|--|--|
| Lifetime L70 (hrs)       | 35000hrs   |  |  |
| Length (mm)              | 66         |  |  |
| Product Type             | Downlights |  |  |
| Operating Temp. (Max) °C | 40°C       |  |  |

## Compliance & Approvals:

## Warranty

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.