



Product Description:

ANOVI UNIVERSAL 6W 120mm 3-Way Surface Dimmable Colour Switchable Downlight Adjustable Round Matt Black

ANOVI UNIVERSAL PROFILE LED ceiling light round matt black 3 heads. Mounted with LED UP UNIVERSAL SWITCH white 2700K/3000K/4000K, CRI90, 6W, 500/525/600lm (88lm/W), low luminance honeycomb 60°, 230VAC/27VDC. Lifespan: 35,000 hours. Dimmable: Yes, TRIAC dimming. Protection class II/III, IP20, 100mm wired, H05S-K. Installation/installation method: surface-mounted. Dimensions: diameter 66mm. Fixing type: screws onto the support. Material: aluminum. Operating temperatures: -20°C/+40°C. Installation

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
29331016	6	2700/3000/4000	500/525/600	8.34209e+007	60	Matt Black	Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Colour switchable between 2700/3000/4000K
- SDCM5
- CRI90
- 35000hr lifetime
- 5 year warranty

Product Specs:

Input Voltage	~230V AC	Input Frequency	50/60HZ
IP Rating	IP20	Lifetime L70 (hrs)	35000hrs
Length (mm)	540	Overall Diameter (mm)	66
Product Type	Downlights	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.