

## Technical Specification

Product Code: DPSS472WH

Description: 2 Gang MiniGrid® Unfurnished Architrave Plate - 2 Apertures



### General Information

Plate Dimensions (mm)	35 (W) x 150 (H) x 8 (D)
Dimensions With Gasket (mm)	38 (W) x 153 (H) x 9 (D)
Plate Fixing Centres - Horizontal (mm)	120.6
MiniGrid Plate (Gang)	2
MiniGrid Single Width Module Quantity	2
MiniGrid Double Width Module Quantity	0
Style	Rounded Profile
Finish	Stainless Steel
Insert Colour	White
Gasket Colour	White
Materials	Front Plate: Stainless Steel Terminals: Brass Earth Strap: Mild Steel
Anti Microbial Certified	No
Termination Type	Screw
Modular Rocker Switches	Yes
Minimum Back Box Depth (mm)	25
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	10

Insert: Urea  
Terminal Screws: Steel & Yellow Passivated

**Standards** BS 5733: 2010 +A1: 2014

**Additional Information** Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Interchangeable with modules in the MiniGrid Range.  
Suitable flush mounting back box WA672

