

## **Technical Specification**

Product Code: DPSS722WH

**Description:** 20A Ingot Double Pole Plate Switch





## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W)  $\times$  91 (H)  $\times$  9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

Style Rounded Profile Finish Stainless Steel

Insert Colour White Gasket Colour White

Materials Front Plate: Stainless Steel

Switch Cover: Stainless Steel
Terminal Screws: Steel & Yellow Passivated

lettiina Sciews. Steel & fellow Passivateo

Internal Busbars: Formed Pressed Brass

Insert & Housing: Urea Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20
Termination Type Screw
Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5

Double Pole Switch Yes

Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40
Warranty (Years) 10

**Standards** BS EN 60669-1: 2018

Terminal Torque Value (Nm) 1.8

## **Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



