




Product Description:

OrbitalCWS[™] 15-28W Colour & Wattage Switchable IP66 Bulkhead


Three colour temperatures and three wattages in one product! Being IP66 rated makes this new OrbitalCWS[™] ideal for outdoor and damp locations. Additionally, this product offers plug and play emergency and microwave sensor packs making the range perfect for the wholesaler to control stock levels and store less products, whilst also being simple for the contractor to convert on site. 54 product combinations in one!

SKU Code	Wattage	ColorTemp	Lumens	BeamAngle	SKUType	FinishColor
AU-BH28CWSW	15	3000K	1500	120	Non Dimmable	White
AU-BH28CWSW	15	4000K	1600	120	Non Dimmable	White
AU-BH28CWSW	15	6500K	1500	120	Non Dimmable	White
AU-BH28CWSW	22	3000K	2200	120	Non Dimmable	White
AU-BH28CWSW	22	4000K	2300	120	Non Dimmable	White
AU-BH28CWSW	22	6500K	2200	120	Non Dimmable	White
AU-BH28CWSW	28	3000K	2800	120	Non Dimmable	White
AU-BH28CWSW	28	4000K	2800	120	Non Dimmable	White
AU-BH28CWSW	28	6500K	2800	120	Non Dimmable	White
AU-BH28CWSBLK	15	3000K	1400	120	Non Dimmable	Black
AU-BH28CWSBLK	15	4000K	1500	120	Non Dimmable	Black
AU-BH28CWSBLK	15	6500K	1400	120	Non Dimmable	Black
AU-BH28CWSBLK	22	3000K	2200	120	Non Dimmable	Black
AU-BH28CWSBLK	22	4000K	2300	120	Non Dimmable	Black
AU-BH28CWSBLK	22	6500K	2200	120	Non Dimmable	Black
AU-BH28CWSBLK	28	3000K	2800	120	Non Dimmable	Black
AU-BH28CWSBLK	28	4000K	2800	120	Non Dimmable	Black
AU-BH28CWSBLK	28	6500K	2800	120	Non Dimmable	Black


Line Drawing



Polar Curve



Colour



Feature & Benefits

- Colour switchable between 3000K, 4000K and 6500K
- Wattage switchable between 15W, 22W and 28W
- IP66 rated
- IK10 rated
- -20 to +45 ambient operating temperature
- Plug and play emergency, emergency self-test and microwave sensing packs available
- 5 Year Warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	50000hrs
Lamp Base	None
Weight (Kg)	1.262
Product Type	Bulkheads
Operating Temp. (Max) °C	45°C

Input Frequency	50/60HZ
IP Rating	IP66
IK Rating	IK10
Overall Diameter (mm)	360
Projection (mm)	105
Operating Temp. (Min) °C	-20°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.