

## RSeries™ FIRE RATED DOWNLIGHTS

### SUPER QUICK TOOL-FREE INSTALLATION




Scan to watch  
Installer Video

UP TO 24 COMBINATIONS


Up to 105lm/W **FASTFIX™**



Adjustable Bezel



Colour  
Switchable



Wattage  
Switchable

Loop in, loop out push terminals for fast wiring of either solid or stranded cable

Screwless cable strain relief, simply close the cap to secure the cables

Supplied with White SUPER SLIM IP65 Polycarbonate Bezel

Bezel Options:



\*Add suffix MB, PC or SN for Matt Black, Polished Chrome or Satin Nickel finishes.



Scan to View  
Full RSeries Range



Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Horz.Adj	Cutout [Ø]
<b>R6CWS™ Colour &amp; Wattage Switchable Triac Dimmable Adj (IP65 when used with IP65 Bezel)</b>							
<b>AU-R62CWSFF</b>	4W	3000-5700K	420lm	105	60°	20°	70mm
	6W	3000-5700K	620lm	103	60°	20°	70mm

Bezel Options

**AU-R62BZ** R6™CWS Adjustable IP65 Polycarbonate Bezel

**3 hour Emergency pack AU-FRLM10EMB available**

Lumen value based on 4000K



**Insulation coverable**

Downlight and driver are insulation coverable - no accessory or insulation cut-out is required.



Suitable for use with i-joists,  
metal web & solid timber joists

Visit [auroralighting.com/ijoist](http://auroralighting.com/ijoist)

