



# Z LED ECO

Z LED ECO Highbay 1 Cool White

Code: AZLE1/1/CW

|               |  |
|---------------|--|
| Category      | High/Low Bay                               |
| Application   | Ancillary, Hospitality, Industrial, Retail |
| Specification | Performance                                |



## PRODUCT FEATURES

- Sleek and robust LED low/high bay for industrial applications and ancillary areas
- Lensed diffuser design helps to control the beam angle, offering better light distribution
- Integral on-board driver reduces the overall size and weight of product, resulting in a slim, lightweight and easy to install unit
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- High efficiency up to 120lm/w
- Installation eye-bolt supplied as standard
- IP65 and IK06 ratings

| GENERAL INFORMATION     |              |
|-------------------------|--------------|
| Wattage                 | 100W         |
| Lumens Delivered        | 11000lm      |
| Lm/W                    | 120lm/W      |
| Beam Angle              | 90           |
| CRI                     | 80           |
| CCT                     | 4000K        |
| Input                   | 220/240V     |
| Operating Temp          | -45°C - 45°C |
| SDCM                    | 6            |
| UGR                     | 28           |
| Energy efficiency class | E            |

| TECHNICAL INFORMATION          |                     |
|--------------------------------|---------------------|
| Light Source                   | LED                 |
| Colour / Finish                | Black               |
| IP Rating                      | IP66                |
| Class Protection               | 1                   |
| Internal / External            | Internal / External |
| Surface / Recessed / Suspended | Surface, Suspended  |
| Lumen Depreciation L70 B50     | L70 B50 54,000h     |
| Warranty (Years)               | 3                   |
| CE Mark                        | Yes                 |
| Diameter                       | 253 mm              |
| Height                         | 80 mm               |

