

ARCHITECTURAL DOWNLIGHTS SPECIFICATION SHEET



BDL10F30WM

Sleek, low glare, baffled downlight

FEATURES

IP rating	IP44
Colour flexibility	Fixed colour
Tilttable	Fixed
Rotation angle	NR
UGR	11
Dimmable	Mains
Input	Mains AC
LED Lifetime	70,000h L70 B10
CRI	>90Ra
SDCM	3SDCM
Flicker Free	Yes
Emergency version available	Yes

INSTALLATION INFORMATION

Install Connector Type	Loop in, loop out
Insulation Coverable	No
Cut Out Size	65-68mm
Bathroom zone	1
Inrush Current	2.6A/0.3ms
Construction Material	Aluminium
Maximum ceiling thickness	40mm
Weight	240g
Maximum ambient temperature	40°C
SELV	Yes
Building regulations	Part P, L, C, E
Electric Class [1, 2, 3]	2

PHOTOMETRICS @ 25°C

Product code	Finish	Feature I	Feature II	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
BDL10F30WM	Matt White RAL9003	Slim Bezel	Black Baffle	9.6W	3000K	50°	625	65	1136

WIRING INFORMATION

Cable Required for Connector	1061 x twin & earth (6242Y 3x1.5mm ²) or 3-core cable (R02V 3x1.5mm ²)
Type of Wiring Required	Parallel

ACCESSORIES

LEDEP10	3hr non-maintained, self-test emergency pack (plug & play)	Sold Separately
BDLFH2	Fire hood	Sold Separately



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Black baffle & CRI 90+ for a low glare and high-quality appearance, showing colours and textures in their best light.

Choice of fixed or adjustable function, allows you to direct light exactly where it is required.

Mains, 1-10V or DALI dimming options for flexibility and integration with control systems.

Comes with rolled spring clips and plug & play connectors to support ease of installation.

7 year warranty: Collingwood's signature quality you can trust.

Wide beam angle, perfect for consistent light distribution of open areas.

Slim and discreet flat metal bezel.

Easy-fit connector included.

Mains loop-in loop-out

Beam angle:

