

Commercial Bollard

NEW

High output, multi-directional LED lighting



1190 & 1990
LUMENS



BI-DIRECTIONAL
LIGHT OUTPUT



IP66 RATED
PROTECTION



IK10 DURABLE
CONSTRUCTION

- Bi-directional output, including optional side cover (JC17077) for single direction option*
- Ultra efficient, up to 1990 lumen output
- -40°C to +50°C operating temperature
- Ideal for commercial pathways, open spaces & perimeter building illumination
- Supplied with 'J' bolts for concrete installations
- 5yr extended warranty, register at jcc.co.uk



*Side cover sold separately.

For more information, contact
your local ASM or visit jcc.co.uk.

JCC | a **LEVITON**
company

Commercial Bollard



High output, multi-directional LED lighting



Ultra efficient, up to 1990 lumen output

Our Commercial Bollard is ultra efficient, with up to 1990 (24W) & 1190 (14W) lumen outputs.



Single or bi-direction output

Includes optional side cover* (JC17077) for areas that don't require dual illumination.



Designed for tough conditions

IK10 & IP66 rated, suitable for a variety of applications that are open to the elements.



Ideal for commercial spaces

Suitable for public pathways, open spaces and perimeter building illumination.

- -40°C to +50°C operating temperature
- Die-cast aluminium construction
- Supplied with 'J' bolts for concrete installations
- 5yr extended warranty, register at jcc.co.uk

CODE	DESCRIPTION	COL TEMP.	WATT	LUMENS
JC17078	Commercial Bollard 500mm	4000K	14W	1190
JC17079	Commercial Bollard 900mm	4000K	14W	1190
JC17080	Commercial Bollard 500mm	4000K	24W	1990
JC17081	Commercial Bollard 900mm	4000K	24W	1990
JC17077*	Side cover accessory	-	-	-

For more information, contact your local ASM or visit jcc.co.uk.