



LOUR FIRST ORDER

## THE QUICK AND EASY ALTERNATIVE FOR MR16 INSTALLATIONS

All in One solution - Easy to install No need for a lamp holder or transformer



**50mm Diameter** (same as GU10/MR16 lamps)

- O Low profile only 29mm high
- o 240V no need for separate driver
- Easy Fit with 28cm cable and loop-in/loop-out connector
- Compatible with Dimmable and Non-Dimmable circuits







certification by UKAS Warringtonfire



Includes Fast-Fit screwless - push-fit junction box for tool-free assembly



WITHOUT JUNCTION BOX

| Product Code      | Watts | Temp K | Lumens | Dim | Beam | Junction Box |
|-------------------|-------|--------|--------|-----|------|--------------|
| ILMDC001          | 3.8W  | 2700   | 410lm  | Yes | 36°  | -            |
| ILMDE002          | 3.8W  | 4000   | 420lm  | Yes | 36°  | -            |
| WITH JUNCTION BOX |       |        |        |     |      |              |
| ILMDC003          | 3.8W  | 2700   | 410lm  | Yes | 36°  | Yes          |
| ILMDE004          | 3.8W  | 4000   | 420lm  | Yes | 36°  | Yes          |





Evolight fitted in a downlight

