



01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

# Arc

Wallpack suitable for 3m (10W) or 4m (17W) mounting height

## Features

<b>IK rating</b>	IK10
<b>IP rating</b>	IP66
<b>Colour flexibility</b>	Colour switchable
<b>Sensor</b>	PC Dusk to Dawn
<b>Dimmable</b>	No
<b>Input</b>	220-240V 50/60Hz
<b>LED Lifetime</b>	54,000h L70
<b>Flicker Free</b>	Yes
<b>Emergency version available</b>	Yes

## Installation information

<b>Inrush Current</b>	16A 0.2ms
<b>Construction Material</b>	ADC12 Aluminium alloy, uv-resistant polycarbonate lens, stainless steel 304 screws
<b>Weight</b>	2.6kg
<b>Maximum ambient temperature</b>	-30°C to +50°C
<b>Electric Class (1, 2, 3)</b>	1

## Photometrics @ 25°C

Product code	Finish	Feature I	Feature II	W	Colour	Beam	lm	lm/W	EM
ARA1N	Anthracite grey RAL7016	Standard	10W	10W	3000K	98°114°	1550	155	-
ARA1N	Anthracite grey RAL7016	Standard	10W	10W	4000K	98°114°	1650	165	-
ARA1N	Anthracite grey RAL7016	Standard	10W	10W	5000K	98°114°	1600	160	-
ARA1NE	Anthracite grey RAL7016	Emergency	10W	10W	3000K	98°114°	1550	155	300
ARA1NE	Anthracite grey RAL7016	Emergency	10W	10W	4000K	98°114°	1650	165	300
ARA1NE	Anthracite grey RAL7016	Emergency	10W	10W	5000K	98°114°	1600	160	300
ARA2N	Anthracite grey RAL7016	Standard	17W	17W	3000K	98°114°	2600	153	-
ARA2N	Anthracite grey RAL7016	Standard	17W	17W	4000K	98°114°	2750	162	-
ARA2N	Anthracite grey RAL7016	Standard	17W	17W	5000K	98°114°	2700	159	-
ARA2NE	Anthracite grey RAL7016	Emergency	17W	17W	3000K	98°114°	2600	153	300
ARA2NE	Anthracite grey RAL7016	Emergency	17W	17W	4000K	98°114°	2750	162	300
ARA2NE	Anthracite grey RAL7016	Emergency	17W	17W	5000K	98°114°	2700	159	300

## Accessories

<b>AREMGKIT</b>	Arc Emergency Spare Kit	Sold Separately
-----------------	-------------------------	-----------------

## Guarantee

5 years guarantee

## Features & benefits

Designed to illuminate a pathway efficiently and safely, whilst preserving the habitat

Highly energy efficient with up to 165 luminaire lumens per watt for low total cost over luminaire's lifetime

Anti-glare optical control designed to reduce upward sky glow

Set to 3000K as standard (CCT switchable) to minimise low blue light content

Integral photocell to switch the light ON at dusk and OFF at dawn

Slim 97mm profile integrates discreetly to the building architecture

Removeable backplate to aid fast installation

Light source energy efficiency:



Beam angle:

