## **Residential** specification sheet









# **H2 Sense**

Fire-rated downlight within integral PIR and switched live out functionality

#### **Features**

IP rating	IP65 (from below) IP20 (from above)
CSP Switchable	Yes, CCT
Tiltable	N/A
Rotation Angle	N/A
UGR	28
Sensor Option	PIR
Dimmable Option	No
LED Lifetime	44,000h L70 B10
CRI	80 Ra
SDCM	3 SDCM

#### Installation information

Install Connector Type	Integrated terminals, loop-in/loop-out	
Insulation Coverable	Rolled and blown insulation	
Double Insulation	Yes	
Cut Out Size	Ø 68-72mm	
UK Bathroom Zone	1	
Inrush Current	<5A 0.15ms	
Construction Material	Steel and Polycarbonate	
Maximum ceiling thickness	40 mm	
Weight	0.22kg	
Maximum Ambient Temperature	-10°C to 40°C	
SELV	Yes	
<b>UK Building Regulations</b>	Part B, C, E, P & L	
Ceiling Joist Approvals	Solid timber, I-Joist and Metal Web	
Electric Class (1, 2, 3)	2	

#### Photometrics @ 25°C

Product code	Finish	w	Colour	Beam	lm	llm/W	lx @ 1m
DLSENSE	Bezel sold separately	6W	2700K	50°	600	100	590
DLSENSE	Bezel sold separately	6W	3000K	50°	650	108	635
DLSENSE	Bezel sold separately	6W	4000K	50°	675	113	630

## Wiring information

Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²) or 3-core cable (R02V 3x1.5mm²)
Type of Wiring Required	Parallel


## Accessories

DLSENWBEZP	H2 Sense White Bezel with PIR	Sold Separately
DLSENWBEZ	H2 Sense White Bezel without PIR	Sold Separately
DLSENBBEZP	H2 Sense Black Bezel with PIR	Sold Separately
DLSENBBEZ	H2 Sense Black Bezel without PIR	Sold Separately



01604 495 151 collingwoodlighting.com







#### Guarantee

5 year warranty

## Features & benefits

Colour switchable between 2700K, 3000K and 4000K

PIR downlight for switching those lights OFF in your home that keep getting left ON

High efficacy up to 113lm/W

Hold time - adjust from 30secs up to 15 minutes

Sensitivity - Adjust from close range of 10cm up to 2 metres away

Lux Level - Adjust to keep the light OFF when there is enough natural daylight

Switched live out to other lights

Fire-rated Downlight

Bezel sold seperately

Light source energy efficiency:



## Beam angle: 50°

