



Product Description: UtiliteXL™ 30W IP65 Wall Pack


Designed to last in a tough environment, the UtiliteXL™ wall pack with cast aluminium base and polycarbonate diffuser is available in standard, microwave sensor, photocell and emergency versions with black housing.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-WP103/40	30	4000	2550	85	120	Black	Non Dimmable
EN-WP103EM/40	30	4000	2550	85	120	Black	Emergency
EN-WP103PH/40	30	4000	2550	85	120	Black	Photocell

Line Drawing

Polar Curve

Color



Product Features:

- IP65 wall pack with cast aluminium base and polycarbonate diffuser.
- IK10 rating
- Non-dimmable with integrated LED driver
- Suitable for walkways, stairways, general amenity & security areas.
- SEAI: EN-WP103/40 - LIG84989
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	50000	IK Rating	IK10
Lamp Base	None	Width (mm)	264
Length (mm)	309	Height (mm)	309
Weight (Kg)	1.965	Product Type	Wall Lights
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	45°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.