






01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

GL040 Ultra low glare

2W, 215lm ground light

Features

IK rating	IK08
IP rating	IP68
CSP Switchable	Fixed colour
UGR	<10
Walk Over / Drive Over	Walk over
LED Lifetime	70,000h L70
SDCM	3 SDCM

Installation information

Cut Out Size	Ø 70mm
UK Bathroom Zone	1
Construction Material	Brass
Weight	0.7
Maximum Ambient Temperature	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	W	Colour	Beam	lm	lm/W	lx @ 1m
GL040AMBL27	2W	2700K	34°	200	100	645
GL040AMBL30	2W	3000K	34°	208	104	671
GL040ANBL27	2W	2700K	12°	200	100	2689
GL040ANBL30	2W	3000K	12°	208	104	2797

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLU/350 1-9	220-240V	Yes	No	1	1	3
PLR/350 1-5	N/A	Yes	No	0	1	1
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	3

Accessories

JB2 / JB4 / JB6	IP68 Boxes	Sold Separately
TUBE/68	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
CW Smart	Compatible Smart System	Sold Separately
GLA01	Converter plate	Sold Separately

Guarantee

7 year extended warranty

Features & benefits

- 2W at 350mA or 700mA
- Baffled for low glare and visual comfort
- Low voltage groundlight
- Single LED and lens combination for maximum efficiency and optimal light distribution
- Marine grade stainless steel 316 or antique brass
- Long lifetime of 70,000hrs
- 7 year warranty

Light source energy efficiency:



Beam angles: 12° 34°

