

STRIP AND DRIVER KIT IP67 5M 3500K 12V 6W/M 325LM/M 60LED/M 10MM WIDTH 115 BEAM BOX PACK WITH 12V IP20 40W DRIVER INTEGRAL

ILSTWHIC064W



This Integral LED 5M Strip and Driver Kit combines our 5 meter IP67 warm white LED strip and 40W 12V constant voltage LED driver. Integral LED warm white LED strip has 60 LEDs per metre and is constructed using high quality materials to ensure a consistent light and colour across the strip. This LED strip is IP67 rated and is suitable for indoor and outdoor applications. Each 5m reel is supplied with an easy-to-follow installation guide and 20x mounting clips. Additional accessories are available, to suit specific installation requirements. The kit also contains Integral LED 40W 12V constant voltage LED driver operates 200-240VAC input range. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use. When installing outdoors, please make sure the driver is used with appropriate outdoor fitting.

Details

| | |
|--------------------------|----------------------|
| Quick Order Code: | 34119 |
| Barcode: | 5055788227908 |
| Category: | Strips |
| Range Name: | Strip And Driver Kit |
| Product Type: | White strip |
| Warranty (Years): | 3 |
| CE RoHS: | Yes |

Physical Data

| | |
|-------------------------------|--|
| Product Width (mm): | 10 |
| Product Weight (g): | 596 |
| Material: | Strip: PCB / Silicone, Driver: Plastic Shell |
| Construction: | LED surface mounted on to strip |
| Strip Cut Points (mm): | 50 |
| Max Run Length (m): | 5 |
| Strip length (M): | 5 |
| Strip Width (mm): | 8 |

Electrical Data

| | |
|---|-----------|
| Power Consumption per meter (W/m): | 6 |
| Voltage (V): | 12 |
| Watts per metre: | 3.1W - 6w |

| | |
|-----------------------------|--|
| Dimming: | Dimmable |
| Driver Included: | Yes |
| Electric Current: | AC |
| Protection Function: | Short Circuit, overload and overheating protection on driver |
| LVD Certified: | Yes |

Light Data

| | |
|---|------------------------------|
| Luminous efficacy (lm/W): | 50 |
| Lumens per meter (lm/m): | 325 |
| Correlated Colour Temperature (CCT) (K): | 3500 |
| Colour Temperature Name: | Warm White |
| Beam Angle: | 115 |
| Colour Rendering Index (CRI): | 80 |
| Colour Type: | White |
| LED Size (mm): | 3528 |
| LED Type: | Surface mounted device (SMD) |
| LEDs per meter: | 60 |
| Lifetime (hours): | 13000 |
| Reel Length (m): | 5 |

Environment

| | |
|--|-----|
| LVD Certified: | Yes |
| CE RoHS: | Yes |
| Lowest Operating Temperature (°C): | -20 |
| Maximum Operating Temperature (°C): | 45 |

Packaging

| | |
|-----------------------------|-----|
| Package Weight (g): | 855 |
| Package Length (mm): | 355 |
| Package Width (mm): | 220 |
| Package Depth (mm): | 40 |