

Features:

Input Voltage: 100 – 240Vac
 Input Frequency: 50/ 60Hz
 Output Power: 4W
 Fully encapsulated with IP66 rating
 Protections: Short circuit/ Overload/ Over Temp.
 Compact and light-weight plastic case
 3 year warranty



Specification:

Model		ECP4-350IF	ECP4-500IF	ECP4-700IF
Output	Rated Current	350mA	500mA	700mA
	Current Accuracy	±10%	±10%	±10%
	Constant Current Region	3-12V	3-9.5V	3-6V
	Max off load voltage	17V	14V	9.5V
	Rated Power	4.2W	4.75W	4.2W
Input	Voltage Range	90-264VAC		
	Frequency Range	50-60Hz		
	Power Factor	≥0.4		
	Efficiency	≥78%	≥75%	≥72%
	Inrush Current (typ.)	60A at 230VAC		
	No Load Power Consumption	<0.3W	<0.3W	<0.3W
Protection	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed		
	Overload	>110% rated output power Hiccup mode, recovers automatically after fault condition is removed		
Environment	Working temp	-20°C – 50°C		
	Working humidity	45–90 % RH non - Condensing		
Safety & EMC	Safety standards	EN61347-1, EN61347-2-13, UL8750, IP66		
	EMC emission	EN55015, EN61000-3-2, FCC PART 15		
	EMC Immunity	EN61547		
Other	Dimensions	38x 30x 23.5		
	Packing	0.045kg; 400pcs/19.8kg		

Dimensions:

