

FAÇADE LIGHTS SPECIFICATION SHEET



LEDLINE 400 110

110° wall washing light bar

FEATURES

IK rating	IK02
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	180°
Dimmable	Yes with suitable driver.
Input	700mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	1
Construction Material	Anodised aluminium
Weight	0.8kg
Maximum ambient temperature	40°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
LEDLINE 400 NW 110	Black	16W	4000K	110°	1000	63	422
LEDLINE 400 WW 110	Black	16W	3000K	110°	750	47	316
LEDLINE 400 27 110	Black	16W	2700K	110°	730	46	308

WIRING INFORMATION

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	1	1
PL/IP/700 3-9	N/A	Yes	No	1	1	1
PLD UNI-DRIVE 700MA	N/A	Yes	Yes (1-10V)	2	1	1

ACCESSORIES

JB4 / JB6	Gel filled junction box
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
WCR 275 BLACK	2-core rubber cable
ULBRACKET	2-piece black anodised aluminium bracket



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

/collingwoodlighting

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Robust cable for permanent use outdoors
Wide beam angle ideal for wall wash

Beam angle: 110°

