Lumi-Fit™

High performance LED downlights

Description

The new range of dimmable Lumi-Fit™ commercial downlights deliver up to an impressive 100lm/W. Supplied with remote driver and fitted with an acrylic diffuser to reduce glare and for even light distribution. With multiple wattages and sizes on offer this range meets the needs for countless new commercial applications or an upgrade for compact fluorescent fittings in existing applications.

Features & Benefits

- Low cost energy saving alternative to compact fluorescent fittings
- Life not affected by frequent switching e.g. when used with occupancy controls
- Plug and play remote driver for easy installation
- DALI plug and play driver available to order
- IP54 rated - suitable for use in commercial offices, educational, council buildings and public toilets
- 1.5kV surge protection
- **3 year warranty**

Up to 100 lm/W

up to 4380 Lumens
L70 40,000 Hours

EM

DALI compatible

NEW **EN-DDLH413**
13W High Performance **IP54**
Dimmable LED Downlight

NEW **EN-DDLH618**
18W High Performance **IP54**
Dimmable LED Downlight

Cat. No.	Watts	Beam	Colour	Lumens	lm/W	L70 Life (hrs)	Overall [Ø]	Cutout [Ø]	Recess	CFL Subst.
EN-DDLH413/40	13W	100°	4000K	1230lm	95	40,000	145mm	120mm	70mm	1 x 26W
EN-DDLH618/40	18W	100°	4000K	1800lm	100	40,000	190mm	160mm	70mm	2 x 18W
EN-DDLH818/40	18W	100°	4000K	1800lm	100	40,000	228mm	200mm	70mm	2 x 18W
EN-DDLH825/40	25W	100°	4000K	2500lm	100	40,000	228mm	200mm	70mm	2 x 26W
EN-DDLH840/40	40W	100°	4000K	4000lm	100	40,000	228mm	200mm	70mm	2 x 32W
EN-DDLH1045/40	45W	100°	4000K	4380lm	97	40,000	280mm	230mm	77mm	2 x 32W

3000K available to special order
For **Emergency** or **DALI** options please contact sales office

Technical Information

Ra >80 COLOUR RENDERING

IP54 ErP COMPLIANT L1 L2

NEW **EN-DDLH825**
25W High Performance **IP54**
Dimmable LED Downlight

NEW **EN-DDLH840**
40W High Performance **IP54**
Dimmable LED Downlight

NEW **EN-DDLH1045**
45W High Performance **IP54**
Dimmable LED Downlight