



WALL LIGHTS SPECIFICATION SHEET




**COLLINGWOOD
LIGHTING**

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

WL075

Silver straight to mains, high output LED wall light

FEATURES

IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	No
Dimmable	No
Input	220-240V 50/60Hz
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
Weight	1.2kg
Maximum ambient temperature	40°C
Electric Class (1, 2, 3)	1

GUARANTEE / WARRANTY

7 year extended warranty available

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution.

Straight to mains wall light, perfect for framing entrances and illuminating columns

Quality brushed aluminium finish

Long lifetime of 70,000hrs

7 year warranty

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
WL075SNBM27	Silver	5.7W	2700K	12°	515	90	2763
WL075SNBM30	Silver	5.7W	3000K	12°	520	91	2789
WL075SNBM40	Silver	5.7W	4000K	12°	530	93	2843
WL075BNBM27	Black	5.7W	2700K	12°	515	90	2763
WL075BNBM30	Black	5.7W	3000K	12°	520	91	2789
WL075BNBM40	Black	5.7W	4000K	12°	530	93	2843
WL075ZNBM27	Bronze	5.7W	2700K	12°	515	90	2763
WL075ZNBM30	Bronze	5.7W	3000K	12°	520	91	2789
WL075ZNBM40	Bronze	5.7W	4000K	12°	530	93	2843

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

ACCESSORIES

N/A	No accessories required
-----	-------------------------

Beam angle:

