WALL LIGHTS SPECIFICATION SHEET



WL140A F

Straight to mains LED wall light

FEATURES

IP rating	IP65
Colour flexibility	Fixed colour
Tiltable	90°
Rotation angle	350°
Dimmable	Yes
Input	220-240V 50/60Hz
LED Lifetime	70,000h L70 B10
CRI	>80Ra
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	15A 0.5ms
Construction Material	Anodised aluminium
Weight	0.7kg
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	1

COLLINGWOOD

- 01604 495 151 collingwoodlighting.com
- f /collingwoodlighting

(C) collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Equivalent to 50W halogen Complete with wall fixings and waterproof crimp connectors Adjustable angle to direct light Cowl design to reduce glare Suitable for indoor and outdoor use

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	ևx Թ 1m
WL140A F NW	Black	8W	4000K	38°	520	65	1471
WL140A F WW	Black	8W	3000K	38°	413	52	1168
WL140A F 27	Black	8W	2700K	38°	400	50	1135

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER


Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	N/A	N/A	N/A	N/A	N/A	N/A

ACCESSORIES

N/A

No accessories required

Beam angle: 38°



208mm

