

PRODUCT DATASHEET

Centorio 12W Downlight

PRODUCT DATA

Range	LED Downlights
Part Code(s)	R098801
Applications	Interior
Warranty	3 years
Certification(s)	CE, RoHS

PHYSICAL DATA

Colour Finish	White Polished Chrome Satin Nickel (all bezels included)
Dimensions (mm)	Ø110 x H37 (hole size 95mm)
Luminaire Fixing	Recessed
Construction Material	Aluminium
Diffuser Type	Polycarbonate - TPa rated
Unit Weight	0.26Kg

ELECTRICAL DATA


Wattage	12W
Voltage Range	AC180-240
Power Factor	>0.90
Inrush Current	<10A
Running Current	DC350mA

PERFORMANCE DATA


Colour Temperature	3000K 4000K 5000K
	840 Lm (3000K)
Lumens (±5%)	860 Lm (4000K)
	960 Lm (5000K)
Efficacy	~70Lm/W (3000K)
	~80Lm/W (4000K)
	~71 Lm/W (5000K)
Operating Temperature	-20°C to +45°C
Beam Angle	80°
Operating Hours	>50000
CRI	>80Ra
IP Rating	IP54
IK Rating	IK07



ALL BEZELS INCLUDED



37mm



110mm
95mm Hole size



R09-88

Remote Control:
Up to 400
downlighters in 4
individually switched
circuits; up to 100
downlighters per
channel

Dimming

Turning the wall switch on/off in quick succession, will change the colour temperature / dimming. The cycle order will be : 3000K, 4000K, night light and then 5000K

Alternatively a remote can control can be purchased serperately to smooth dim down to 3%
- Part Code R09-88